

3-Line Business IP Phone with HD Voice Quality

- TI Chipset, Codec License Included
- 3 Lines, Multi-language, SMS
- 4 Context-sensitive Keys, 10 DSS Keys
- 132x64 LCD, Voicemail, PoE Optional



Yealink SIP-T26P is a professional IP phone which aims to provide business users a cost-effective solution. Equipped with the leading TI VoIP voice engine, it helps to make users proficient and confident in performing common telephone tasks. It features fashion and sleek design, abundant telephony applications, broad interoperability with the popular 3rd party VoIP products. Meanwhile it supports superior wideband codec G.722 which enables excellent HD Voice. Combined with all of these features SIP-T26 definitely fulfill the VoIP deployment needs from enterprise and ITSP.

Network Features

SIP v1(RFC2543), v2(RFC3261)
3 User accounts
NAT Transverse: STUN mode
IP Assignment: Static/DHCP/PPPoE
In-Band DTMF, Out-of-Band DTMF, SIP Info
Proxy mode and Peer-to-peer SIP link mode
TFTP/DHCP/PPPoE client
Telnet/HTTP server
DNS client
NAT/DHCP server
Support VLAN, QoS
PoE(Power over Ethernet)

Voice Features

Wideband Codec: G.722, voice spectrum between 50-7000Hz
Narrowband Codecs: G.711, G.726, G.723.1/iLBC, G.729AB and GSM
VAD, CNG, AEC, PLC, AJB, AGC
Full-duplex hands-free speakerphone
-compliant with IEEE 1329
Support Hearing Aid Compatible (HAC)

Security

Secure RTP
Digest authentication using MD5/MD5-sess
Secure configuration file via AES encryption

Telephony Features

Call Hold, Call Waiting, Call Transfer, Call Forward
Caller ID, Call List, DND, Redial, Flash
3-way Conference, Speed Dial
MP3 Ring Tone Selection, Voicemail
Volume Adjustment, Mute, Speakerphone
Logo Customization, Black List, Phone Lock
Admin/User Configuration Mode
Contact List Export/Import
System Log Export/Import
Hotline, Signal Tone Settable
Multi-language

IP PBX System Integration

SMS, BLF/BLA, Paging, Intercom
Downloadable enterprise phonebook
Call Park, Call Pickup, Distinctive Ringtone
Auto-answer, Dial Plan, Dial-now

Config, Upgrade and Usage

Language Customization Support
Auto-provision: TR069 Optional *
Browser/Console/Telnet/Auto-provision/Keypad
Firmware Upgrade: TFTP/Console/Auto-provision
Direct IP call without SIP proxy
Dial number via SIP server
Dial URL via SIP server

Physical Features

TI Titan Chipset
LCD: 132x64 with white backlit
13 programmable keys with LED
4 text-sensitive keys
23 hard keys, 3 indication LEDs
Headset port: RJ9
Speaker: 8Ohm/1Watt
Network Interface: 2xRJ45 10/100M ports
Expansion Module Port *
Dimension: 273x204x42mm
Weight: 1.05kg
Power adapter: Input: AC 100~240V
Output: DC 5V/1A
Operating humidity: 10~95%
Storage temperature: up to 60°C

Package Features

Qty/CTN: 5 PCS
N.W/CTN: 7.87kg
G.W/CTN: 9.00kg
Measurement: 0.033CMB
Carton Meas: 470*287*222MM

Certifications



Note: * means the features will be done in the future

