

### ***Cost Effective Enterprise IP Phone with 2 Lines***

- TI Chipset, Codec License Included
- 2 Lines, 2x16 LCD
- SMS, Voicemail, PoE Optional



Yealink expands its lineup of IP phones with a new entry-level product SIP-T20. It features a two-line display and 5 hard keys for controlling the various functions. It allows users to make calls in a simple, convenient and reliable manner with an excellent price-performance ratio. SIP-T20 is easy to install and inexpensive to start up, it can be reliably integrated into various SIP-based network solutions. It is ideally suited for environments in which basic business features are required.

## Network Features

SIP v1(RFC2543), v2(RFC3261)  
2 User accounts  
NAT Transverse: STUN mode  
IP Assignment: Static/DHCP/PPPoE  
In-Band DTMF, Out-of-Band DTMF, SIP Info  
Proxy mode and Peer-to-peer SIP link mode  
TFTP/DHCP/PPPoE client  
Telnet/HTTP server  
DNS client  
NAT/DHCP server  
Support VLAN, QoS  
PoE optional

## Voice Features

Wideband Codec: G.722, voice spectrum between 50-7000Hz  
Narrowband Codecs: G.711, G.726, G.723.1/iLBC, G.729AB and GSM  
VAD, CNG, AEC, PLC, AJB, AGC  
Full-duplex hands-free speakerphone

## Telephony Features

Call Hold, Call Waiting, Call Transfer, Call Forward  
Caller ID, Call List, DND, Redial, Flash  
3-way Conference, Speed Dial  
Personal Ring Tone, Voicemail  
Volume Adjustment, Mute, Speakerphone

## IP PBX System Integration

Dial Plan, Dial-now, Paging  
Downloadable enterprise phonebook  
Call Park, Call Pickup, Distinctive Ringtone  
Auto-answer, intercom

## Config, Upgrade and Usage

Firmware Upgrade: TFTP/Console/Auto-provision  
Auto-provision: TR069 Optional  
Direct IP call without SIP proxy  
Dial number via SIP server  
Dial URL via SIP server

## Security

Secure RTP  
Digest authentication using MD5/MD5-sess  
Secure configuration file via AES encryption

## Physical Features

TI Titan Chipset  
LCD: 2 Lines, 2x16  
2 programmable keys  
23 hard keys, 2 indication LEDs  
Headset port: RJ9  
Network Interface: 2xRJ45 10/100M ports  
Dimension:185 X 200 X 90mm  
Net Weight:0.77kg  
Power adapter: Input: AC 100~240V  
Output: DC 5V/1A  
Operating humidity: 10~95%  
Storage temperature: up to 60°C

## Package Features

Qty/CTN: 10 PCS  
N.W/CTN:22.86KG  
G.W/CTN:25.26KG  
Measurement: 0.073CMB  
Carton Meas: 565 x 550 x 235MM

## Certifications

