

DEFENDER[®]
Unlike any other UPS!

Tejus[®]

Highest Value

950



Surge Protected ONLY Receptacles
These receptacles offer protection against lightning, surges, spikes and noise.



RS-232/USB Interface
Monitor UPS status and power management



Battery Power Supplied Receptacles
All plugged equipment are powered by batteries during a power failure.



Modem/Phone Line Surge Protection
Protection for your phone & modem

- Green topology, saves 50% energy on AC mode.
- Built-in super smart charger, 90% charged in 4 hours.
- Charging capability at low input voltage.
- Microprocessor control guarantees high reliability.
- In-built Automatic Voltage Regulator(170-280VAC).
- Simulated sine wave.
- USB communication port and RJ-45 phone line protection.
- Battery backup and surge protected outputs.
- UK and IEC receptacles to meet local requirements.
- Optional coax-protection for TV antenna/ network.



DEFENDER[®]

Unlike any other UPS!

| | |
|------------------------------------|--|
| MODEL | Tejus 950 |
| INPUT | |
| Voltage | 110/120 VAC or 220/230/240 VAC |
| Voltage Range | 85-140 VAC / 170-280 VAC |
| Frequency Range | 50 Hz or 60 Hz (auto sensing) |
| OUTPUT | |
| AC Voltage Regulation (Batt. Mode) | ± 10% |
| Frequency Range (Batt. Mode) | 50 Hz or 60 Hz ± 1 Hz |
| Transfer Time | Typical 2-6 ms, 10 ms max. |
| Waveform (Batt. Mode) | Simulated Sine Wave |
| BATTERY | |
| Battery Type & Number | 12 V/9 AH x 1 |
| Typical Recharge Time | 4 hours to recover up to 90% capacity |
| INDICATORS | |
| AC Mode | Continuous Green |
| Battery Mode | Flashing Yellow |
| Fault | Continuous Red |
| PROTECTION | |
| Full Protection | Overload, discharge, and overcharge protection |
| ALARM | |
| Battery Mode | Beep every 10 seconds |
| Low Battery | Beep every second |
| Overload | Beep every 0.5 second |
| Battery Replacement Alarm | Beep every 2 seconds |
| Fault | Continuous Alarm |
| PHYSICAL | |
| Output Receptacles | 4UK + 2IEC |
| Dimension, D X W X H (mm) | 292 x 199 x 91 |
| Net Weight (kgs) | 5.88 |
| ENVIRONMENT | |
| Humidity | 0-90 % RH @ 0- 40°C (non-condensing) |
| Noise Level | Less than 40dB |
| MANAGEMENT | |
| USB Port | Supports Windows 98 SE/ME/NT 4.x/2000/2003/XP/Vista/2008 |
| Optional RS-232 Port | |



VENCE (Pte) Ltd. No. 22, Dudley Senanayake Mw. (Castle St), Colombo 08, Sri Lanka.
 Phone: +94(0)11-77 VENCE Fax: +94(0)11-77-VENFX
 E-mail: sales@venceip.com Order: www.venceip.com Corporate: www.vencesystem.com